










MGF HYBRID 1S

Cod. AS-075-EX1

Semi-wet 0.75 Hp suction pump, maximum flow rate 1.100 l /min, underpressure 120 mbar. The high reliability of the centrifugal separation system guarantees correct operation of the suction pump for several years. The pump impellers are made of aluminum and guarantee maximum reliability over time. The HYBRID 1S model is also available with amalgam separator (code AS-075-EX-AS).

 Maximum simultaneous use: 1

 Dental Chairs: 2

 Air capacity		 Motor	 Voltage Hz	 Noise Level	 Duty Cycle	max Oper. Head	 Size	 net Weight
m ³ /min 0.0011	l/min 1.1	kW 550.63	230V 50Hz	db(A) 63	100 %	mbar 120/140	mm 530x320x350	Kg 15

Maintenance kits

Kit.	Description	Type	Hours
AS-50060240	<p>HYBRID 1, HYBRID 2 annual maintenance kit</p> <p>Comprehends:</p> <ul style="list-style-type: none"> - Water collector - AS-50060214, 1 quantity - Non-return valve, water separator - AS-50060220, 1 quantity - 1.2 m of PVC pipe for water separation - Information Sheet 	Ordinary	1y
AS-50060210	<p>Hybrid 1,2,5 extraordinary maintenance kit</p> <p>The extraordinary maintenance kit includes: liquid separator impeller, non-return valve, 15 mm fitting (with O-ring), clip and information sheet.</p>	Ordinary	4.000h/4y