



## SAFETY DATA SHEET

**1. Identification of the Substance and Company**  
**TST Control Class 6 Emulating Indicators**  
Product No. See Chart Below  
MSDS No. B117

*NFPA 704 HAZARD RATING:*

*HEALTH: 0*  
*FIRE: 0*  
*REACTIVITY: 0*

Prepared by: Mike Ebers  
[asksteris\\_msds@steris.com](mailto:asksteris_msds@steris.com)

Date Created: September 01, 2009 Date Revised: April 8, 2011 Date Reviewed: N/A

STERIS Corporation, P.O. Box 147, St. Louis, Mo 63166, US  
Emergency Telephone No. 1-314-535-1395 (STERIS); 1-800-424-9300 (CHEMTREC)  
Telephone Number for information: 1-800-444-9009 (Customer Service-Scientific Products)

Albert Browne Limited, Chancery House, 190 Waterside Road, Hamilton Industrial Park,  
Leicester, LE5 1QZ, UK  
Emergency Phone No: +44 (0) 1895 622 639  
Product/Technical Information Phone No: +44 (0) 116 276 8636

Product Number	Cycle Parameters	Shipping Information
2302	Exposure Parameters 121°C for 15 Minutes Steam	Not Restricted
2340	Exposure Parameters 134°C for 3.5 Minutes Steam	Not Restricted
3702	Exposure Parameters 134°C for 9 Minutes Steam	Not Restricted

TST Control Class 6 Emulating Indicators are not hazardous products according to the OSHA Hazard Communication Standard, 29 CFR 1910.1200 and the Controlled Products Regulations; and are free of lead and other heavy metals.

TST Control Class 6 Emulating Indicators do not contain any components derived from animal origin, do not come into contact with materials of animal origin and therefore comply with the "Note for guidance of minimizing the risk of transmitting animal spongiform encephalopathy agents via human Veterinary medicinal products (EMEA/410/01 Rev. 2-October 2003)."

TST Control Class 6 Emulating Indicators are free of latex and natural dry rubber products.

TST Control Class 6 Emulating Indicators are cycle verification indicators which integrate all the critical parameters of the steam sterilization cycle (temperature, saturated steam and exposure time).

TST Control Class 6 Emulating Indicator should be stored in unopened or resealed packages in cool (0-30°C) dry (20-60% RH) conditions away from direct sunlight.